



- Complete protection against dust and liquids IP68
- Washable, sterilized in just seconds, no seams or crevices
- Resistant against most common disinfectants and detergents
- Low force and precise feedback key technology
- Rugged shock protected chassis
- Low noise typing
- Compact size, ergonomically low profile design
- Damage protected key design
- Magnetic fixing option

Switching technology: Carbon pills on gold contact
 Number of Keys: 105 (incl. 12 function keys)
 Protection: IP68 (NEMA 4X)
 Key travel: 1,25 mm
 Actuation force: 1,2 N
 Life: approx. 2 Mio. actuations
 Chassis: desktop (silicone rubber surface)
 Interface: USB
 Power: 20mA@5VDC
 Dimensions: 392 x 141 x 12 mm
 Weight: 1 kg
 Temperature: -20°C to +70°C
 Humidity: up to 100%
 Shock: 3x11 ms pulses (50g) on each of 3 axes
 Vibration: 0,04g/Hz, 20Hz-2kHz, 3 hours
 Certifications: CE, FCC Class15, Part B

Part number	Product name	Features
PS00580	K1-IND-USB-GER	USB, German Layout
PS00581	K1-IND-USB-US	USB, US Layout

Additional versions and modifications are available on request!

Made by ProKeys e.K.
 Karlsbader Straße 1
 08321 Zschorlau
 Phone +49 (0)3771-5644 356
 Fax +49 (0)3771-5644 357
www.prokeys.de
info@prokeys.de